

SABANCI ÜNİVERSİTESİ
KARO HALI TEKNİK ŞARTNAMESİ

01.11.2023

A- TEKNİK TANIMLAR TEKNİK ÖZELLİKLER

1-SERTİFİKALAR

- a) ISO 9001
- b) 14001
- c) CE
- d) GUT-NR
- e) BRE
- f) LEED

2- ÜRÜN TANIMI / Construction

Tufted multi-height loop pile carpet tile H.lands

3- İPLİK CİNSİ / Pile Material

%100 ECOVINYL polyamide 6 Solution dyed

4- KULLANIM SINIFI / Classification

EN 1307 33/LC1 33.Sınıf,Çok Yoğun Trafik

5- HAV AĞIRLIĞI / Pile Weight

605 gr /m²

6- TOPLAM AĞIRLIK / Total Weight

4120 gr /m²

7- KALICI ANTİSTATİKLİK ÖZELLİĞİ

≤2 KV

8- HAV YÜKSEKLİĞİ / Pile Height

3,9 mm

9- TOPLAM YÜKSEKLİK / Total height

6,5 mm

10- DÜĞÜM SIKLIĞI / Tuft Density

198,374 per m²

11- YANGINA DAYANIKLILIK / Fire Resistance

EN 13501-1 B^{fl}-s1

12- IŞIK HASSASİYETİ / Fastness To Light

≥5

13- ISI DİRENCİ / Thermal Resistance

14- TABAN YAPISI / Secondary Backing

Modified bitumen and polyester fleece. Also available in SOFTbac secondary backing

16- ELEKTROSTATİK ÖZELLİKLER / Transversal Resistance

ISO/DIS 10965 ≤10⁹ Ohm

17- DARBE SESİ EMİCİLİĞİ / Impact Noise Rating

25 dB

18- SES EMİLİMİ / Sound Absorption

ISO 354 Hz 125 250 500 1000 2000 4000 S 0,01 0,04 0,07 0,19 0,29 0,34

19- BOYUTSAL SABİTLİK / Dimensional Stability

EN 986 Max. ≤ 0,2 %

20- TEKERLEKLİ SANDALYE İLE KULLANIMI / Castor Chair Suitability

Minumum R Value ≥ 2,4

21- Permanent Antistatic

ISO 6356 ISO 6356 ≤ 2 kV

22- EBAT / Size

500 mm x 500 mm

B- GÖRSELLER

